

**MODEL 5200E  
TRANSMITTER  
SCHEMATICS**



**tau-tron**  
A UNIT OF  
GENERAL SIGNAL



**MODEL 5200E  
TRANSMITTER  
SCHEMATICS**



5200E TRANSMITTER SCHEMATICS  
Table of Contents

|                                                          |         |
|----------------------------------------------------------|---------|
| Output Amplifier Schematic.....                          | D-57075 |
| Output Amplifier Assembly.....                           | D-57077 |
| Oscillator/Interface Schematic.....                      | D-57085 |
| Oscillator/Interface Assembly.....                       | D-57087 |
| Transmit Generator Schematic.....                        | D-57008 |
| Transmit Generator Assembly.....                         | D-57010 |
| STD & GPIB Interface Schematic.....                      | D-57082 |
| STD & GPIB Interface Assembly.....                       | D-57084 |
| Transmitter Front Panel Control & Display Schematic..... | D-57067 |
| Transmitter Front Panel Control & Display Assembly.....  | D-57355 |
| Transmitter Rear Panel Interface Schematic.....          | C-57184 |
| Transmitter Rear Panel Interface Assembly.....           | C-57186 |
| Transmitter Motherboard Schematic.....                   | E-57056 |
| Transmitter Motherboard Assembly.....                    | D-57058 |



NOTES:  
1. UNLESS OTHERWISE SPECIFIED:  
A. RESISTANCE VALUES ARE IN OHMS,  $\pm 5\%$ ,  $\frac{1}{2}W$ .  
B. CAPACITANCE VALUES ARE IN MICROFARADS.  
2. UNMARKED CAPACITORS ARE .01  $\mu f$ .


| LAST REEDES. USED | UNUSED |
|-------------------|--------|
| L2                |        |
| U12 CR3           |        |
| RP4 Q15           |        |
| R76 T2            |        |
| C36 K3            |        |

REFERENCE DRAWINGS:  
ASSEMBLY: D9545-7077  
FABRICATION: D9405-7070

|                |  |                                                                       |  |                                                        |  |                      |  |                                     |  |
|----------------|--|-----------------------------------------------------------------------|--|--------------------------------------------------------|--|----------------------|--|-------------------------------------|--|
| REFERENCE DES. |  | WHERE APPLICABLE:<br>REMOVE ALL BURRS & BREAK<br>SHARP EDGES TO 1/64. |  | UNLESS OTHERWISE SPECIFIED<br>DIMENSIONS ARE IN INCHES |  | CONTR. NO.           |  | PUBLICATION: C-505-1076             |  |
| LAST USED      |  | UNUSED                                                                |  | TOLERANCES: ANGLES ±                                   |  | DR C <i>Chenault</i> |  | tau-tron<br>Chateaufort, Inc. 01834 |  |
| C36            |  |                                                                       |  | FRACTIONS ±                                            |  | CHK <i>P</i>         |  | DRAWING TITLE                       |  |
| CR3            |  |                                                                       |  | 3 PLACE DECIMALS ±                                     |  | 1-8-80               |  | SCHEMATIC                           |  |
| K3             |  |                                                                       |  | 2 PLACE DECIMALS ±                                     |  | 7-7-80               |  | OUTPUT AMPLIFIER                    |  |
| L2             |  |                                                                       |  | 1 PLACE DECIMALS ±                                     |  | 7-7-80               |  | DRAWING NO.                         |  |
| Q16            |  |                                                                       |  | MATERIAL:                                              |  | APPROVED             |  | 57075                               |  |
| R17            |  |                                                                       |  |                                                        |  | BY DIRECTION OF      |  | SCALE                               |  |
| RP4            |  | TCH: 57077                                                            |  | S2500D VTR                                             |  |                      |  | S2500D T X                          |  |
| T2             |  | NEXT ASSY                                                             |  | USED ON                                                |  |                      |  | SHEET 1 of 2                        |  |
| U12            |  | APPLICATION                                                           |  |                                                        |  |                      |  |                                     |  |




PROPRIETARY NOTICE:  
THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION  
OF TAU-TRON, INC. AND HEREBY THE DOCUMENT IS  
PROPRIETARY INFORMATION SHALL BE FORWARDED, REPRO-  
DUCTION, COPIED OR DISCLOSED WITHOUT THE EXPRESS WRIT-  
TEN PERMISSION OF A DULY AUTHORIZED REPRESENTATIVE  
OF SAID COMPANY.



|                                                                      |  |                                                                                                                                                                 |  |                                                                                       |  |                                  |  |
|----------------------------------------------------------------------|--|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|--|---------------------------------------------------------------------------------------|--|----------------------------------|--|
| WHERE APPLICABLE<br>REMOVE ALL BURRS & BREAK<br>SHARP EDGES TO 1/64. |  | UNLESS OTHERWISE SPECIFIED<br>DIMENSIONS ARE IN INCHES<br>TOLERANCES: ANGLES ±<br>FRACTIONS ±<br>3 PLACE DECIMALS ±<br>2 PLACE DECIMALS ±<br>1 PLACE DECIMALS ± |  | CONTR. NO.<br>DR <i>C Smith</i> 4-5-80<br>CHK <i>P</i> 4-7-80<br>APP <i>W</i> 4-11-80 |  | tau-tron<br>Chelmsford, MA 01934 |  |
| TDC-5707 502000 KMR                                                  |  | APPLICATION                                                                                                                                                     |  | DRAWING TITLE<br>SCHEMATIC<br>OUTPUT AMPLIFIER                                        |  | SCALE 1/8" = 1"                  |  |
| NEXT ASSY USED ON                                                    |  | BY DIRECTION OF                                                                                                                                                 |  | SHEET 2 OF 2                                                                          |  | REV E                            |  |



SEE NOTE 1




NOTES:

1. PLACE THE ASSEMBLY PARTS LIST REVISION MARK ON THE ASSEMBLY IN DESIGNATED AREA.

|                                                  |  |                                                |                                          |
|--------------------------------------------------|--|------------------------------------------------|------------------------------------------|
| E57154 55200D TX<br>REV D 11 MAR 80<br>EQUIPMENT |  | JT 9-16-80<br>B. COOPER 9-18-80<br>WEL 9-18-80 | tau-tion<br>ASSEMBLY<br>OUTPUT AMPLIFIER |
|                                                  |  | 0                                              | 57077<br>2/1 55200D TX (OF)              |



PROPRIETARY NOTICE  
THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION  
OF TAU-TRON, INC. AND RECEIVED THE DOCUMENT FOR SAID  
PROPRIETARY INFORMATION SHALL BE FORWARDED, REPRO-  
DUCED, COPIED OR DISCLOSED WITHOUT THE EXPRESS WRIT-  
TEN PERMISSION OF A DULY AUTHORIZED REPRESENTATIVE  
OF SAID COMPANY.




- NOTES:  
1) UNLESS OTHERWISE SPECIFIED:  
A RESISTANCE VALUES ARE IN OHMS, K=K, M=M, S=S.  
B CAPACITANCE VALUES ARE IN MICROFARADS.  
2) UNMARKED CAPACITORS ARE .01uF.  
3) COMPONENTS TO BE ADDED OR TRIMMED IN  
TEST AS REQUIRED.

|                                                                      |  |                                                                                                                                                                 |  |                                                                                                                                                                 |  |                                                                                                                            |  |
|----------------------------------------------------------------------|--|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|--|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----------------------------------------------------------------------------------------------------------------------------|--|
| WHERE APPLICABLE<br>REMOVE ALL BURRS & BREAK<br>SHARP EDGES TO 1/64" |  | UNLESS OTHERWISE SPECIFIED<br>DIMENSIONS ARE IN INCHES<br>TOLERANCES: ANGLES ±<br>FRACTIONS ±<br>3 PLACE DECIMALS ±<br>2 PLACE DECIMALS ±<br>3 PLACE DECIMALS ± |  | CONT. NO.<br>DR <i>C. Smith</i> 4-1-80<br>CHK <i>P</i> 4-16-80<br>APP <i>W. H. H.</i> 4-16-80<br>D<br>TDK-57087 552000 XMTR<br>NEXT ASSY USED ON<br>APPLICATION |  | DRAWING TITLE<br>OSCILLATOR/INTERFACE PCB<br>SIZE CODE IDENT NO   DRAWING NO<br>D   57087<br>SCALE 1:1 552000 SHEET 1 OF 1 |  |
| TAU-TRON<br>Chino, California, U.S.A.                                |  |                                                                                                                                                                 |  | DRAWING NO. 57087<br>REV. 1                                                                                                                                     |  |                                                                                                                            |  |




| TABLE I<br>JUMPERS |     |
|--------------------|-----|
| FROM               | TO  |
| E9                 | E11 |
| E12                | E10 |



SEE NOTE 1

SEE NOTE 2




# NOTES :

1. PLACE A PERMANENT REVISION LEVEL MARK ON THE ASSEMBLY IN THE DESIGNATED AREA.
2. INSTALL CRYSTAL AFTER SOCKET HAS BEEN INSTALLED.

|                                                        |  |                           |                                                                 |                                                                                          |
|--------------------------------------------------------|--|---------------------------|-----------------------------------------------------------------|------------------------------------------------------------------------------------------|
| E-57158 SS200D TX<br>NEXT ASSY. USED ON<br>APPLICATION |  | APPROVED<br>BY: B. COOPER | C. AITHERTON 1/23/81<br>B. COOPER 1/25/81<br>W. ROLLINS 1/25/81 | tau-tron<br>OSCILLATOR INTFC PCB ASSY<br>D 954 57087<br>SHEET 2/1 SS200D TX SHEET 1 OF 1 |
|--------------------------------------------------------|--|---------------------------|-----------------------------------------------------------------|------------------------------------------------------------------------------------------|




PROPRIETARY NOTICE  
THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION  
OF TAU-TRON, INC. AND NEITHER THE DOCUMENT NOR SAID  
PROPRIETARY INFORMATION SHALL BE PUBLISHED, REPRODUCED,  
COPIED OR DISCLOSED WITHOUT THE EXPRESS WRITTEN  
PERMISSION OF A DULY AUTHORIZED REPRESENTATIVE  
OF SAID COMPANY






PROPRIETARY NOTICE  
THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION  
OF TAU-TRON, INC. AND NEITHER THE DOCUMENT NOR SAID  
INFORMATION SHALL BE DISCLOSED, REPRODUCED,  
OR TRANSMITTED IN ANY FORM OR BY ANY MEANS,  
ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING,  
RECORDING, OR BY ANY INFORMATION STORAGE AND  
RETRIEVAL SYSTEM, WITHOUT THE WRITTEN PERMISSION  
OF TAU-TRON, INC.



|                                                                      |  |                                                                                                                                                                |  |                                                |  |
|----------------------------------------------------------------------|--|----------------------------------------------------------------------------------------------------------------------------------------------------------------|--|------------------------------------------------|--|
| WHERE APPLICABLE<br>REMOVE ALL BURNS & BREAK<br>SHARP EDGES TO 1/64" |  | UNLESS OTHERWISE SPECIFIED<br>DIMENSIONS ARE IN INCHES<br>TOLERANCES ANGLES ±<br>FRACTIONS ±<br>3 PLACE DECIMALS ±<br>2 PLACE DECIMALS ±<br>1 PLACE DECIMALS ± |  | CONTR NO<br>CHK<br>APPROVED<br>BY DIRECTION OF |  |
| TOM-57010 352200 TX<br>NEXT ASSY USED ON                             |  | MATERIAL                                                                                                                                                       |  | tau-tron<br>che mford wa dist                  |  |
| APPLICATION                                                          |  | DRAWING TITLE<br>SCHEMATIC<br>TRANSMIT GENERATOR PCB                                                                                                           |  | SIZE CODE IDENT NO. DRAWING NO.<br>D 57008     |  |
|                                                                      |  |                                                                                                                                                                |  | REV<br>F3                                      |  |
|                                                                      |  |                                                                                                                                                                |  | SHEET 2 OF 2                                   |  |



THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION OF TAD TRON INC AND WHETHER THE DOCUMENT NOR SAID PROPRIETARY INFORMATION SHALL BE PUBLISHED, REPRODUCED, COPIED OR DISCLOSED WITHOUT THE EXPRESS WRITTEN PERMISSION OF A DULY AUTHORIZED REPRESENTATIVE OF SAID COMPANY



|    |                               |                |         |        |
|----|-------------------------------|----------------|---------|--------|
| H  | REV PER ECO# 02033            | TMM 124-85     | 1-1-85  |        |
| J  | UPDATED PER DOC ACCURACY PROG | PER ECO# 02176 | 6-28-85 | 124-85 |
| K  | UPDATED PER ECO# 02181 TB     | 8-8-85         | 1/14/85 | KL     |
| L  | REV PER ECO# 02656            | 8-10-85        | 1/14/85 | KL     |
| L1 | REV PER AUDIT # A0768         | 8-10-85        | 1/14/85 | KL     |

1. PLACE A PERMANENT REVISION LEVEL MARK ON THE ASSEMBLY IN THE DESIGNATED AREA.
2. JUMPERS TO BE #24 AWG BUS WIRE WITH SLEEVING
3. JUMPERS TO BE #26 AWG INSULATED WIRE
4. \* - DENOTES STATIC SENSITIVE DEVICE

65200D TX

SEE P. L.  
9545-7010

3T  
B COOPER  
W. ROWLES

12-31-80  
1-9-81  
1-20-81

ASSEMBLY  
TRANSMIT GENERATOR PCB

954 57010

57010

L1



| DESIG | QTY | INTERFACE | QTY          |
|-------|-----|-----------|--------------|
| 44    | 1   |           | 0 (NOT USED) |
| 45    | 1   |           | 0            |
| 46    | 1   |           | 0            |
| 47    | 1   |           | 0            |
| 48    | 1   |           | 0            |
| 49    | 1   |           | 0            |
| 50    | 1   |           | 0            |
| 51    | 1   |           | 0            |
| 52    | 1   |           | 0            |
| 53    | 1   |           | 0            |
| 54    | 1   |           | 0            |
| 55    | 1   |           | 0            |
| 56    | 1   |           | 0            |
| 57    | 1   |           | 0            |
| 58    | 1   |           | 0            |
| 59    | 1   |           | 0            |
| 60    | 1   |           | 0            |
| 61    | 1   |           | 0            |
| 62    | 1   |           | 0            |
| 63    | 1   |           | 0            |
| 64    | 1   |           | 0            |
| 65    | 1   |           | 0            |
| 66    | 1   |           | 0            |
| 67    | 1   |           | 0            |
| 68    | 1   |           | 0            |
| 69    | 1   |           | 0            |
| 70    | 1   |           | 0            |
| 71    | 1   |           | 0            |
| 72    | 1   |           | 0            |
| 73    | 1   |           | 0            |
| 74    | 1   |           | 0            |
| 75    | 1   |           | 0            |
| 76    | 1   |           | 0            |
| 77    | 1   |           | 0            |
| 78    | 1   |           | 0            |
| 79    | 1   |           | 0            |
| 80    | 1   |           | 0            |
| 81    | 1   |           | 0            |
| 82    | 1   |           | 0            |
| 83    | 1   |           | 0            |
| 84    | 1   |           | 0            |
| 85    | 1   |           | 0            |
| 86    | 1   |           | 0            |
| 87    | 1   |           | 0            |
| 88    | 1   |           | 0            |
| 89    | 1   |           | 0            |
| 90    | 1   |           | 0            |
| 91    | 1   |           | 0            |
| 92    | 1   |           | 0            |
| 93    | 1   |           | 0            |
| 94    | 1   |           | 0            |
| 95    | 1   |           | 0            |
| 96    | 1   |           | 0            |
| 97    | 1   |           | 0            |
| 98    | 1   |           | 0            |
| 99    | 1   |           | 0            |
| 100   | 1   |           | 0            |


| LAST REF DES USED | UNUSED |
|-------------------|--------|
| 518               |        |
| 112               |        |
| 214               |        |
| 512               |        |

- NOTES:
1. UNLESS OTHERWISE SPECIFIED:
    - A RESISTANCE VALUES ARE IN OHMS,  $V_{4W}$ ,  $\pm 5\%$ .
    - E CAPACITANCE VALUES ARE IN MICROFARADS.
  2. ☐ DENOTES PIN CONNECTOR.
  3. COMPONENT TO BE ADDED IN TEST AS REQUIRED; (.01  $\mu$ F CAPACITOR).

|                                                                     |             |                                                                                                                                                                             |  |                                                               |                    |                                    |              |
|---------------------------------------------------------------------|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|---------------------------------------------------------------|--------------------|------------------------------------|--------------|
| WHERE APPLICABLE<br>REMOVE ALL BURRS & BREAK<br>SHARP EDGES TO 1/64 |             | UNLESS OTHERWISE SPECIFIED<br>DIMENSIONS ARE IN INCHES<br>TOLERANCES ANGLES ±<br>FRACTIONS ±<br>3 PLACE DECIMALS ±<br>2 PLACE DECIMALS ±<br>1 PLACE DECIMALS ±<br>MATERIAL: |  | CONTR NO.<br><br>CR _____<br>CHK. _____<br>A _____<br>D _____ |                    | tau-tron<br>electronic test gauges |              |
| TDR- 57219                                                          | 500000 XMYR |                                                                                                                                                                             |  | APPROVED                                                      | SIZE 000H-BEINGRND | DRAW NG NO.                        | REV          |
| TDR- 57084                                                          | 500000 YMYR |                                                                                                                                                                             |  | BY DIRECTION OF                                               | D                  | 57082                              | H            |
| NEXT ASSY USED ON                                                   |             |                                                                                                                                                                             |  |                                                               | SCALE 1/8"         | 500000 XMYR                        | SHEET 1 OF 1 |
| APPLICATION                                                         |             |                                                                                                                                                                             |  |                                                               |                    |                                    |              |



|   |                         |                |
|---|-------------------------|----------------|
| D | REDRAWN PER ECO#123     | REV#2 6-7-81   |
| E | REV PER ECO#01150       | REV#1 8-4-81   |
| F | REV PER ECO#1324        | OPR. 9-4-81    |
| G | REV PER ECO#01484       | REV#1 10-14-81 |
| H | UPDATED PER DR. 1011041 | REV#1 11-11-81 |
| I | MOD. ECU # 02171        | REV#1 11-11-81 |



1. ~~1. PLACE A PERMANENT REVISION LEVEL MARK ON THE ASSY IN THE DESIGNATED AREA.~~
2. ~~2. O DENOTES 0.1UF CAPACITORS.~~
3. ~~3. PLACE A PERMANENT REVISION LEVEL MARK ON THE ASSY IN THE DESIGNATED AREA.~~
4. ~~4. ORIENTATE THE ASSY IN OPPOSITE DIRECTION FROM REMAINING ASSYS.~~

SEE NOTE 3.

COMPONENT SIDE.

E-51154 650000 TA

BUDD 1-2-81  
 WEL 1-9-81  
 ASSEMBLY  
 STD BUS INTERFACE PCB.

945 57084

2-1 650000 TA


1 1

57084



A





|   |                                               |
|---|-----------------------------------------------|
| E | REDRAWN WITH CHANGES<br>REPLACES REV A #02221 |
| C | REV PER ECO # 02575                           |
| - | REV PER AUDIT # A0469                         |

# NOTES:



1. CHANGE ASSY NO FROM 9545-7069 TO 9545-7355. THEN PLACE THE ASSEMBLY PARTS LIST REVISION, ON THE ASSEMBLY IN THE DESIGNATED AREA.
2. STATIC SENSITIVE DEVICES ARE DENOTED BY THE SYMBOL "\*".
3. INSTALL S1 THRU S9 (SWITCHES), AFTER WAVE SOLDERING, WITH PIN LOCATIONS AS SHOWN IN DETAIL B. CLEAN WITH ISOPROPYL ALCOHOL.
4. UNLESS OTHERWISE SPECIFIED THE FOLLOWING APPLY:  
A) ALL JUMPER CABLES TO BE #26 AWG STRANDED INSULATED WIRES.  
B) ALL LED'S REQUIRE SPACERS.
5. REMOVE R1 LOCATED UNDER R15 ON COMPONENT SILK SCREEN.

SEE NOTE 1

|                                                       |  |                                                                                              |  |                                                  |  |
|-------------------------------------------------------|--|----------------------------------------------------------------------------------------------|--|--------------------------------------------------|--|
| PART NO. 57360<br>REV. E 3<br>CHANGE 1 3E             |  | DATE 9/20/80<br>BY CS<br>9/25/80<br>3 PLACE DECIMALS<br>2 PLACE DECIMALS<br>1 PLACE DECIMALS |  | tau-tron<br>NATIONAL DIVISION                    |  |
| D-57360 S5200E TX<br>NEXT ASSY USED ON<br>APPLICATION |  | DATE 9/20/80<br>BY CS<br>9/25/80<br>3 PLACE DECIMALS<br>2 PLACE DECIMALS<br>1 PLACE DECIMALS |  | TRANSMITTER FRONT PANEL<br>CONTROL & DISPLAY PCB |  |
| D-57360 S5200E TX<br>NEXT ASSY USED ON<br>APPLICATION |  | DATE 9/20/80<br>BY CS<br>9/25/80<br>3 PLACE DECIMALS<br>2 PLACE DECIMALS<br>1 PLACE DECIMALS |  | TRANSMITTER FRONT PANEL<br>CONTROL & DISPLAY PCB |  |




DISCLAIMER NOTICE:  
THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION  
TAU-TRON, INC. AND NEITHER THE DOCUMENT NOR SAID  
PROPRIETARY INFORMATION SHALL BE PUBLISHED, REPRO-  
DUCED, COPIED OR DISCLOSED WITHOUT THE EXPRESS WRIT-  
TEN PERMISSION OF A DULY AUTHORIZED REPRESENTATIVE  
OF SAID COMPANY



NOTES:  
1. UNLESS OTHERWISE SPECIFIED:  
A. RESISTOR VALUES ARE IN OHMS,  $\frac{1}{4}W$ ,  $\pm 5\%$ .  
B. CAPACITOR VALUES ARE IN MICROFARADS.

REFERENCE DRAWINGS:  
ASSEMBLY: TCK-57186  
FABRICATION: TCG-57185




|                                                                      |        |                                                                                                                                                                                     |           |               |                            |                                            |  |
|----------------------------------------------------------------------|--------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|---------------|----------------------------|--------------------------------------------|--|
| WHERE APPLICABLE:<br>REMOVE ALL BURRS & BREAK<br>SHARP EDGES TO 1/64 |        | UNLESS OTHERWISE SPECIFIED<br>DIMENSIONS ARE IN INCHES<br>TOLERANCES, ANGLES $\pm$<br>FRACTIONS $\pm$<br>3 PLACE DECIMALS $\pm$<br>2 PLACE DECIMALS $\pm$<br>1 PLACE DECIMALS $\pm$ |           | CONTR NO.     | <br>chalmersford, wa 98004 | DRAWING TITLE                              |  |
| U2                                                                   |        |                                                                                                                                                                                     |           | DR            |                            | SCHEMATIC<br>TX REAR PANEL INTERFACE BOARD |  |
| S1                                                                   |        |                                                                                                                                                                                     |           | CHK'B. Cooper |                            |                                            |  |
| R9                                                                   |        |                                                                                                                                                                                     |           | APP'D         |                            |                                            |  |
| J5                                                                   |        |                                                                                                                                                                                     |           |               |                            | SIZE CODE IDENT NO. DRAWING NO.            |  |
| CR4                                                                  | R3-8   |                                                                                                                                                                                     |           |               |                            | C 57184                                    |  |
| C3                                                                   | CR1    | C-57186                                                                                                                                                                             | S52000 TX |               |                            | SHEET 1 OF 1                               |  |
| LAST USED                                                            | UNUSED | NEXT ASSY                                                                                                                                                                           | USED ON   |               |                            |                                            |  |
| APPLICATION                                                          |        | APPLICATION                                                                                                                                                                         |           |               |                            |                                            |  |



THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION OF TAU-TRON, INC. AND NEITHER THE DOCUMENT NOR SAID PROPRIETARY INFORMATION SHALL BE PUBLISHED, REPRODUCED, COPIED OR DISCLOSED WITHOUT THE EXPRESS WRITTEN PERMISSION OF A DULY AUTHORIZED REPRESENTATIVE OF SAID COMPANY.

|   |                                               |               |     |
|---|-----------------------------------------------|---------------|-----|
| C | ORIG. PER POC 00718                           |               |     |
| A | IN VER. ECU 52524                             |               |     |
| I | RE PER. ECU 52524                             | C.S. 12-29-80 | REC |
| E | RE PER. ECU 52524                             | C.S.          | REC |
| B | REV PER ECONOT 35 M.E.H. 2-21-84              |               |     |
| D | UPDATED PER DOC. RECEIVED<br>PRG. ECO # 02197 |               |     |



1. ~~SEE SHEET 1 FOR WIRING DIAGRAM~~
2. SEE SHEET 2 FOR ~~WIRING DIAGRAM~~
3. WIRING SIDE.  
FOR INFORMATION, THE FOLLOWING  
MARK ON THE ASSEMBLY OF THE DISC-  
MOUNTED ARE:

<sup>4</sup> SEE NOTE 3.

UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN INCHES

D-57144 'S52000 TY

3-2-80  
9-15-80  
9-15-80

ASSEMBLY  
REAR PANEL INTERFACE TX

C. 954 57186 D


5/1. SE2000 T) 072



PROPRIETARY NOTICE

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION OF TAD-TAD, INC. AND NEITHER THE DOCUMENT NOR SAID PROPRIETARY INFORMATION SHALL BE PUBLISHED, REPRODUCED, COPIED OR DISCLOSED WITHOUT THE EXPRESS WRITTEN PERMISSION OF A DULY AUTHORIZED REPRESENTATIVE OF SAID COMPANY.

SEE S-LE-7-85-A



WIRING SLE


5-2-80  
B. Cooper  
4-5-80  
4-5-80

ASSEMBLY  
REAR PANEL INTERFACE TX

D-57144 S52000 TX

C 954 57186 D  
2/1 S52000 TX 2002




[illegible]



# PROPRIETARY NOTICE

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION OF TAD-TRON, INC. AND RECEIVERS THE DOCUMENT FOR SAID PROPRIETARY INFORMATION SHALL BE FURNISHED, REPRODUCED, COPIED OR ENCLOSED WITHOUT THE EXPRESS WRITTEN PERMISSION OF A DULY AUTHORIZED REPRESENTATIVE OF SAID COMPANY.

|   |                                              |                    |       |
|---|----------------------------------------------|--------------------|-------|
| C | REDRAWN PER ECO-01123 B.M.B. 5/5/82          | 5/4/82             | WJ/AM |
| D | REV PER ECO-01121 B.M.B.                     | 1-12-82            | AL/MD |
| E | REV PER ECO-01253 R.R.E. 8/10/82             | 10-12-82           | AAM   |
| F | UPDATED PER DDC ACCURACY<br>PROG ECO # 02/97 | 8/10/83<br>8/11/83 | PK/KE |



## NOTES:

1. ~~UNLESS OTHERWISE SPECIFIED,~~  
~~RESISTANCE VALUES ARE IN OHMS 444455X~~  
~~CAPACITANCE VALUES ARE IN MICROFARADS.~~
2. PLACE A PERMANENT REVISION LEVEL MARK ON THE ASSEMBLY IN THE DESIGNATED AREA.

57377 55200E TX  
57058 55200D TX

C. SMITH 1-8-81  
B. COOPER 1-12-81  
W. POLLINS 1-14-81

ASSEMBLY  
TX MOTHER BOARD PCB.

57058

2/1 552000 TX

F





